

PRODUCT NUMBER P835613

**FABULON SUPER SATIN POLYURETHANE HEAVY DUTY FLOOR FINISH  
OIL MODIFIED FOR PROFESSIONAL USE****DESCRIPTION:**

**FABULON PROFESSIONAL OIL MODIFIED POLYURETHANE FLOOR FINISH SUPER SATIN** provides a highly attractive, tough, durable, gloss luster for virtually all interior wood surfaces, including floors, furniture, doors, cabinets, cupboards and trim. This flexible, clear high gloss finish has exceptional resistance to chipping, peeling, soaps, detergents, water, etc. High quality polyurethane resin assures longer lasting results than regular polyurethane finishes. Hard, fast drying properties permit application of two coats in one day.

**WARNING!** Removal of old paint by sanding, scraping, or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

**TECHNICAL:****TYPE:** Oil Modified Polyurethane**COLOR:** Amber/Clear**LUSTRE:** Super Satin (low eggshell)**DRY TIME:** Dust-free, 2 to 3 hours

Recoat, 4 to 6 hours

Ready to use, 18 to 24 hours

**COVERAGE:** 1 U.S. gallon- approx. 400 to 600 sq. ft.**APPLICATION:** Brush, lambs wool**CLEANUP:** Mineral spirits**NON-VOLATILES:** 44% by weight**SURFACE PREPERATION:**

1. Properly prepare surface according to NOFMA or NWFA specifications.
2. floor is now ready for two (2) or three (3) coats of **FABULON PROFESSIONAL OIL MODIFIED POLYURETHANE FLOOR FINISH SUPER SATIN.**

**STAINING:**

If staining is desired, use an oil based stain. This product will amber "white" or pastel stains. Not recommended for use over "white" or pastel stains. Apply stain according to stain manufacturers instructions.

**NATURAL WOOD & SEALER:**

To seal bare, unstained wood and maintain a natural wood color, a first coat of FABULON PRYME primer and sealer is recommended. Apply PRYME to bare, unstained wood following label instructions. Do not use a steared sanding sealer or shellac.

**APPLICATION:**

Use **FABULON PROFESSIONAL OIL MODIFIED POLYURETHANE FLOOR FINISH SUPER GLOSS** as supplied. Stir, DO NOT agitate or shake, before use. On new work, apply two (2) or three (3) coats evenly with a clean brush or lambs wool applicator. Allow four (4) to six (6) hours dry time between coats. Sand lightly between coats with 120 to 150 grit sandpaper or equivalent abrasive. Clean dust between coats.

**CLEANUP:**

Immediately after use, clean brush or applicator with mineral spirits.

**WARNING!**  
**COMBUSTIBLE LIQUID AND VAPOR. VAPOR HARMFUL.**

**CONTAINS:** Petroleum distillates. Vapor harmful. May affect the brain or central nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation.

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**PRECAUTIONARY MEASURES:** KEEP AWAY FROM HEAT, SPARKS AND FLAME. DO NOT smoke. PREVENT build-up of vapors by opening all windows and doors to achieve cross ventilation. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors, open windows and doors or use other means to ensure fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave area. AVOID contact with eyes and skin. DO NOT take internally.

**STORAGE/HANDLING:** Keep container closed when not removing reducer. Do not reuse container or transfer reducer to any other container. Close container after each use.

**FIRST AID:** *Swallowing* – If swallowed, do not induce vomiting. Call Poison Control Center, Hospital Emergency Room or physician immediately. *Inhalation Overexposure* – If dizziness or nausea occurs, remove person to fresh air and seek medical attention. *Eye Contact* – Flush eyes immediately with plenty of water for at least 15 minutes. Get medical attention immediately. *Skin Contact* – Wash skin thoroughly with warm water and soap.

**FOLLOW ALL PRECAUTIONS IN THE WORK AREA AND ALL ADJACENT AREAS. BE SURE THAT ALL PERSONS UNDERSTAND AND FOLLOW ALL PRECAUTIONS.**

**KEEP OUT OF REACH OF CHILDREN.**

**NOTICE TO PURCHASER**

Our only obligation shall be to replace or refund for any material proved to be defective. The suitability of the product for an intended use shall be up to the user. You may have other rights which vary from state to state.

*A Heritage of Fine Wood Finishes Since 1849*

FABULON PRODUCTS, 101 Prospect Ave. NW, Cleveland, OH 44115

Revised 6/2007

**DELTAQUIP**  
www.deltaquip.ca (604) 298-8996 SUPPLIES LTD.